

INDUSTRIAL COMPONENT DATA

PT-IQ-4X1-24DC-PT 2801271 PHOENIX CONTACT Surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT-IQ-4X1-24DC-PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT-IQ-4X1-24DC-PT
Catalog number	2801271
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-1A3B2D5A52
Generated	2026-08-04

Product Overview

Surge protection device

Surge protection, consisting of plug-in protection and base element, with indica. Multi-level diagnostics and status integrated in module for four signal conductors with joint reference potential.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2801271

Packing unit 1 pc

Catalog page Page 111 (C-4-2017)

GTIN 4046356766531

Weight per Piece (excluding packing) 123.530 g

Custom tariff number 85363030

Country of origin DE (Germany)

Dimensions

Height 109.3 mm

Width 17.7 mm

Depth 77.5 mm (incl. DIN rail 7.5 mm)

Horizontal pitch 1 Div.

Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Altitude ≤ 4000 m (amsl (above mean sea level))

Degree of protection IP20

General

Housing material PA 6.6

Flammability rating according to UL 94 V-0

Color jet black RAL 9005

Mounting type DIN rail: 35 mm

Type DIN rail module, two-section, divisible

Direction of action Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground

Additional descriptions

Note Remote signaling as well as the power supply of the DIN rail connector are established by snapping the module into place on the DIN rail connector.

Protective circuit

IEC test classification C1

C2

C3

D1

Nominal voltage UN 24 V DC

Maximum continuous voltage UC 30 V DC

21 V AC

Rated current 700 mA (50 °C)

Operating effective current ICat UC ≤ 1 mA (per path)

Residual current IPE ≤ 1 mA (per path)

Nominal discharge current In(8/20) μs (line-earth) 10 kA

Pulse discharge current Iimp(10/350) μs (line-earth) 2.5 kA

Total discharge current Itotal(8/20) μs 20 kA

Voltage protection level Up(line-earth) ≤ 75 V (C1 - 1 kV/500 A)

≤ 135 V (C2 - 10 kV / 5 kA)

≤ 55 V (C3 - 25 A)

<=....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT-IQ-4X1-24DC-PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.