

INDUSTRIAL COMPONENT DATA

LIT 1X2-24 2804610 PHOENIX CONTACT Surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: LIT 1X2-24



Manufacturer	PHOENIX CONTACT
MPN / Reference	LIT 1X2-24
Catalog number	2804610
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-AFA5830510
Generated	2026-07-29

Product Overview

Surge protection device

Overvoltage protection. In module p/ mounting on SIM rail. One piece, 6.2 mm wide, for a circ. Floating signal in 2 cond. technique. Tested according to degrees of protection. in Ex zones: Ex ia IIC/Ex iaD. Suitable for HART.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Trabtech (TT)**

Additional Product Information

Key Commercial Data

Orderkey 2804610

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 100 (C-4-2017)

GTIN 4046356428330

Weight per Piece (excluding packing) 53.000 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 93.1 mm

Width 6.2 mm

Depth 102.5 mm (incl. DIN rail 7.5 mm)

Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude $\leq$ 2000 m (amsl (above mean sea level))

Degree of protection IP20

General

Housing material PBT

Flammability rating according to UL 94 V-0

Color anthracite grey RAL 7016

Mounting type DIN rail: 35 mm

Type DIN rail module, one-piece

Direction of action Line-Line & Line-Earth Ground

Protective circuit

IEC test classification C1

C2

C3

D1

Nominal voltage UN 24 V DC

Maximum continuous voltage UC 36 V DC

25 V AC

Rated current 350 mA (40° C)

Operating effective current ICat UC $\leq$ 2 μ AResidual current IPE $\leq$ 2 μ ANominal discharge current $I_n(8/20)$ μ s (line-line) 5 kANominal discharge current $I_n(8/20)$ μ s (line-earth) 5 kAPulse discharge current $I_{imp}(10/350)$ μ s (line-earth) 500 A

1 kA (in total)

Total discharge current $I_{total}(8/20)$ μ s 10 kA

20 kA (1x)

Max. discharge current $I_{max}(8/20)$ μ s maximum (line-line) 10 kAMax. discharge current $I_{max}(8/20)$ μ s maximum (line-earth) 10 kA

20 kA (in total)

Nominal pulse current $I_{an}(10/1000)$ μ s (line-line) 50 ANominal pulse current $I_{an}(10/1000)$ μ s (line-earth) 50 A

100 A (in total)

Output volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LIT 1X2-24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.