

INDUSTRIAL COMPONENT DATA

VAL-MS 120 ST 2807586 PHOENIX CONTACT Type 2 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 120 ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-MS 120 ST
Catalog number	2807586
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	10 Pcs
Document ID	EO-3AE7028BC7
Generated	2026-08-03

Product Overview

Type 2 surge protection plug

Plug-in type 2 surge protection with high-power varistor for VAL-MS base element, with thermal control, optical fault indication. Execution: 120 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2807586

Packing unit 10 pc

Catalog page Page 58 (C-4-2017)

GTIN 4017918075279

Weight per Piece (excluding packing) 34.400 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 52.4 mm

Width 17.5 mm

Depth 55.3 mm

Horizontal pitch 1 Div.

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude $\leq$ 2000 m (amsl (above mean sea level))

Permissible humidity (operation) 5 % ... 95 %

Shock (operation) 25g (Half-sine / 11 ms / 3x $\pm$ X, $\pm$ Y, $\pm$ Z)

Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

General

IEC test classification II

T2

EN type T2

IEC power supply system TN

Mode of protection L-N

L-PEN

Mounting type on base element

Color jet black RAL 9005

Housing material PA 6.6

Degree of pollution 2

Flammability rating according to UL 94 V-0

Type DIN rail module, two-section, divisible

Number of positions 1

Arrester can be tested with CHECKMASTER from software version: From SW rev. 1.10

Surge protection fault message optical

Protective circuit

Nominal voltage UN 120/208 V AC (TN)

Nominal frequency fN 50 Hz (60 Hz)

Maximum continuous voltage UC 150 V AC

Residual current IPE $\leq$ 0.45 mA

Standby power consumption PC $\leq$ 70 mVA

Nominal discharge current $I_n(8/20)$ μ s 20 kA

Maximum discharge current $I_{max}(8/20)$ μ s 40 kA

Short-circuit current rating ISCCR 25 kA

Voltage protection level Up $\leq$ 0.9 kV

Residual voltage Ures $\leq$ 0.9 kV (at I_n)

$\leq$ 0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 120 ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.