

INDUSTRIAL COMPONENT DATA

VAL-MS 230 IT ST 2807599 PHOENIX CONTACT Type 2 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 230 IT ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-MS 230 IT ST
Catalog number	2807599
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	1 Pcs
Document ID	EO-0225E67D1F
Generated	2026-08-01

Product Overview

Type 2 surge protection plug

Plug-in type 2 surge protection with high-power varistor for VAL-MS base element, with thermal control, optical fault indication. Execution: 230 V AC (IT system)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2807599

Packing unit 10 pc

Catalog page Page 59 (C-4-2017)

GTIN 4017918075286

Weight per Piece (excluding packing) 47.550 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 52.4 mm

Width 17.5 mm

Depth 55.3 mm

Horizontal pitch 1 Div.

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude ≤ 2000 m (amsl (above mean sea level))

Permissible humidity (operation) 5 % ... 95 %

Shock (operation) 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)

Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

General

IEC test classification II

T2

EN type T2

IEC power supply system TN

TT

IT

Mode of protection L-N

L-PE

L-PEN

Mounting type on base element

Color jet black RAL 9005

Housing material PA 6.6

Degree of pollution 2

Flammability rating according to UL 94 V-0

Type Male

Number of positions 1

Arrester can be tested with CHECKMASTER from software version: From SW rev. 1.10

Surge protection fault message optical

Additional descriptions

Note Usable in all low-voltage systems between L-N or L-PEN.

Only usable in IT Systems between L-PE, if the exposed-conductive-parts (bodies) of the equipment of the low-voltage installation is connected to the earthing arrangement of the transformer substation. (interconnected earthing arrangement of the HV-transformer substation with the bodies of the LV-installation. RE= RA accordance to IEC 60364-4-442....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 230 IT ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.