

## INDUSTRIAL COMPONENT DATA

# VAL-MS 320-UD ST 2858315 PHOENIX CONTACT Type 2 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 320-UD ST



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                                   |
| MPN / Reference | VAL-MS 320-UD ST                                                  |
| Catalog number  | 2858315                                                           |
| Category        | Accessories/spare parts for surge protection power supply systems |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-C1DC971190                                                     |
| Generated       | 2026-08-03                                                        |

## Product Overview

Type 2 surge protection plug

Plug-in protection against type 2 surges with high power varistor for VAL-MS base element, with thermal control, optical defect indication. Execution: 320 V AC

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                 |
|--------------|---------------------------------|
| Catalog path | PHOENIX CONTACT > Trabtech (TT) |
|--------------|---------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 2858315

Packing unit 10 pc

Catalog page Page 61 (C-4-2017)

GTIN 4017918878054

Weight per Piece (excluding packing) 43.530 g

Custom tariff number 85363030

Country of origin DE (Germany)

Dimensions

Height 52.4 mm

Width 17.5 mm

Depth 55.3 mm

Horizontal pitch 1 Div.

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude  $\leq$  2000 m (amsl (above mean sea level))

Permissible humidity (operation) 5 % ... 95 %

Shock (operation) 25g (Half-sine / 11 ms /  $3x \pm X, \pm Y, \pm Z$ )

Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

General

IEC test classification II

T2

EN type T2

IEC power supply system TN

TT

Mode of protection L-N

L-PEN

Mounting type on base element

Color jet black RAL 9005

Housing material PA 6.6

Degree of pollution 2

Flammability rating according to UL 94 V-0

Type DIN rail module, two-section, divisible

Number of positions 1

Arrester can be tested with CHECKMASTER from software version: From SW rev. 1.10

Surge protection fault message optical

Protective circuit

Nominal voltage UN 240/415 V AC (TN)

240/415 V AC (TT)

Nominal frequency fN 50 Hz (60 Hz)

Maximum continuous voltage UC 335 V AC

Residual current IPE  $\leq$  0.45 mA

Standby power consumption PC  $\leq$  150 mVA

Nominal discharge current  $I_n(8/20)$   $\mu$ s 20 kA

Maximum discharge current  $I_{max}(8/20)$   $\mu$ s 40 kA

Short-circuit current rating ISCCR 25 kA

Voltage protection level Up  $\leq$  1.5 kV

Residual voltage Ure...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 320-UD ST with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.