

INDUSTRIAL COMPONENT DATA

PT 2X1-24AC/FM-ST 2920146 PHOENIX CONTACT Surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2X1-24AC/FM-ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2X1-24AC/FM-ST
Catalog number	2920146
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-0945A82180
Generated	2026-08-03

Product Overview

Surge protection plug

Pluggable surge protection with status indication integrated in the module and remote indication contact for two signal conductors with common reference potential. Rated voltage: 24 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2920146

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 91 (TT-2011)

GTIN 4046356154062

Weight per Piece (excluding packing) 27.540 g

Custom tariff number 85363010

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Height 44.8 mm

Width 17.5 mm

Depth 51.7 mm

Horizontal pitch 1 Div.

Complete module height 90 mm

Complete module width 17.7 mm

Complete module depth 65.5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Degree of protection IP20

General

Housing material PA 6.6

Flammability rating according to UL 94 V-0

Color black

Standards for clearances and creepage distances VDE 0110-1

IEC 60664-1

Mounting type on base element

Type Male

Direction of action Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground

Protective circuit

IEC test classification C1

C2

C3

D1

VDE requirement class C1

C2

C3

D1

Nominal voltage UN 24 V AC

Maximum continuous voltage UC 40 V DC

28 V AC

Rated current 300 mA (45°C)

Operating effective current $I_{Cat UC} \leq 5 \mu A$

Residual current $I_{PE} \leq 1 \mu A$ (with PT 2X1+F-BE)

$\leq 10 \mu A$ (Directly grounded)

Nominal discharge current $I_n(8/20) \mu s$ (line-earth) 10 kA

Pulse discharge current $I_{imp}(10/350) \mu s$ 2.5 kA (per path)

Total discharge current $I_{total}(8/20) \mu s$ 20 kA

Max. discharge current $I_{max}(8/20) \mu s$ maximum (line-earth) 10 kA

Nominal pulse current $I_{an} (10/1000) \mu s$ (line-earth) 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2X1-24AC/FM-ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.