

INDUSTRIAL COMPONENT DATA

PT 2X1-24DC-ST 2856087 PHOENIX CONTACT Surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2X1-24DC-ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2X1-24DC-ST
Catalog number	2856087
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-BBE732A3DA
Generated	2026-08-03

Product Overview

Surge protection plug

Plug-in surge protection for base element, coarse and fine protection for two signal conductors with common reference potential, coarse protection against longitudinal voltage to earth. Workmanship: 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 2856087

Packing unit 10 pc

Catalog page Page 112 (C-4-2017)

GTIN 4017918599164

Weight per Piece (excluding packing) 20.100 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 44.8 mm

Width 17.5 mm

Depth 51.7 mm

Horizontal pitch 1 Div.

Complete module height 90 mm

Complete module width 17.7 mm

Complete module depth 65.5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Degree of protection IP20

General

Housing material PA 6.6

Flammability rating according to UL 94 V-0

Color black

Standards for clearances and creepage distances VDE 0110-1

IEC 60664-1

Mounting type on base element

Type Male

Direction of action Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground

Arrester can be tested with CHECKMASTER from software version: From SW rev. 1.00

Protective circuit

IEC test classification C1

C2

C3

D1

VDE requirement class C1

C2

C3

D1

Nominal voltage UN 24 V DC

Maximum continuous voltage UC 28 V DC

20 V AC

Rated current 300 mA (45°C)

Operating effective current ICat UC ≤ 5 µA

Residual current IPE ≤ 1 µA (with PT 2X1+F-BE)

≤ 10 µA (Directly grounded)

Nominal discharge current In(8/20) µs (line-earth) 10 kA

Pulse discharge current Iimp(10/350) µs 2.5 kA (per path)

Total discharge current Itotal(8/20) µs 20 kA

Max. discharge current Imax(8/20) µs maximum (line-earth) 10 kA

Nominal pulse current Ian (10/1000) µs (line-earth) 30 A

Output voltage limitation at 1 kV/µs (line-earth) sp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2X1-24DC-ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.