

INDUSTRIAL COMPONENT DATA

S 0308359 PHOENIX CONTACT Switching lock

Brand: PHOENIX CONTACT | Manufacturer Part Number: S



Manufacturer	PHOENIX CONTACT
MPN / Reference	S
Catalog number	0308359
Category	Installation clamp for meters
Minimum order	100 Pcs
Document ID	EO-921C20203F
Generated	2026-07-29

Product Overview

Switching lock

Connection blocker, for sliding skid, length: 12 mm, width: 8.2 mm, color: white

Switching lock, for disconnect slides, width: 8.2 mm, height: 12 mm, color: white

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Switching lock

Data management status

Article revision 00

DimensionsWidth 8.2 mm

Height 12 mm

Material specificationsColor white (RAL 9010)

Material PA

Flammability rating according to UL 94 V2

Insulating material PA

Relative insulation material temperature index (Elec., UL 746 B) 125 °C

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (storage/transport) 30 % ... 70 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.