

INDUSTRIAL COMPONENT DATA

TC-XC96-AO16-EX-PS-HIMAX01 2908748 PHOENIX CONTACT Termination Carrier for connecting 16 MACX Analog Ex i si..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TC-XC96-AO16-EX-PS-HIMAX01



Manufacturer	PHOENIX CONTACT
MPN / Reference	TC-XC96-AO16-EX-PS-HIMAX01
Catalog number	2908748
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-268F2F9BF3
Generated	2026-08-05

Product Overview

Termination Carrier for connecting 16 MACX Analog Ex i signal conditioners to analog output cards of the HIMA HImax controller, via one C96 connector, 96-pos. Suitable for the HImax X-AO 16 01 card, with HART multiplexer connection

Termination Carrier for the connection of 16 MACX Analog Ex-i separation amplifiers to analog output cards of the HIMA-HImax control system, via a C96, 96-pole connector. Suitable for HImax X-AO 16 01 card, with HART multiplexer connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2908748

Packing unit 1

GTIN 4055626328218

Custom tariff number 85366990

Drawings

General

Connection 1

Connection 3

Dimensions

Environmental Product Compliance

[Classifications](#)

[Note](#)

[Supply](#)

[Connection 2](#)

[Ambient conditions](#)

[Standards and Regulations](#)

[Set Items](#)

[Drawings](#)

[Block diagram](#)

[Back to top](#)[Note](#)

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

[Back to top](#)[General](#)

Nominal voltage $U_N < 50 \text{ V DC}$ (Per signal/channel)

Max. permissible current 1 A (Signal/channel)

[Back to top](#)[Supply](#)

Designation Device supply

Input voltage 24 V DC

Input voltage range 19.2 V DC ... 30 V DC

Input current $\leq 2 \text{ A}$

Redundant supply yes, decoupled from diodes

Polarization and surge protection Yes

Output name Switching output

Contact type 1 N/C contact (alarm = open)

Maximum switching voltage 30 V DC (2 A)

Fuse 2x 2.5 A Slow-blow (exchangeable)

Status display 2x green LEDs (PWR1 and PWR2)

[Back to top](#)[Connection 1](#)

Connection name Power supply

Connection method Screw connection

Stripping length 7 mm

Number of connections 1

Number of positions 6

Conductor cross section solid 0.75 mm² ... 2.5 mm²

Conductor cross section flexible 0.75 mm² ... 2.5 mm²

Conductor cross section AWG 18 ... 14

[Back to top](#)[Connection 2](#)

Connection name Controller level

Connection in acc. with standard IEC 60603-2

Connection method Pin strip

Type C

Number of connections 1

Number of positions 96

[Back to top](#)[Connection 3](#)

Connection method IDC/FLK pin strip

Number of conne...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TC-XC96-AO16-EX-PS-HIMAX01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.