

INDUSTRIAL COMPONENT DATA

TC-XC96-DO32-PS-P-HIMAX01 2908920 PHOENIX CONTACT Termination Carrier for connecting the 24/32 PSR-PS 22 cou..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TC-XC96-DO32-PS-P-HIMAX01



Manufacturer	PHOENIX CONTACT
MPN / Reference	TC-XC96-DO32-PS-P-HIMAX01
Catalog number	2908920
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-19EC029EB4
Generated	2026-08-06

Product Overview

Termination Carrier for connecting the 24/32 PSR-PS 22 coupling relay to the HIMA HImax controller digital output cards. Suitable for the HImax X-DO 24 01 and X-DO 32 01 cards. Solution for Emergency Shut Down (ESD) applications. Termination Carrier for the connection of 24/32 PSR-PS22 coupling relays to digital output cards of the HIMA HImax control system. Suitable for HImax X-DO 24 01 and X-DO 32 01 cards. Solution for Emergency Shut Down (ESD) applications.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Technical dataNotes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

Utilization restriction

EMC note EMC: class A product, see manufacturer's declaration in the download area

Product propertiesProduct type Module carrier

Data management status

Article revision 05

Insulation characteristics: Air clearances and creepage distances

Insulation Basic insulation

Overvoltage category II

Pollution degree 2

Electrical properties Max. permissible current 0.5 A (Signal/channel)

Nominal voltage UN < 50 V DC (Per signal/channel)

Air clearances and creepage distances

Rated insulation voltage 30 V

Rated surge voltage 0.5 kV

Supported controller HIMA HIMax

Suitable I/O card X-DO 32 01

Supply

Designation Device supply

Note Feed-in via MINI MCR-SL-PTB (2864134) power module and MINI MCR-SL-PTB-FM fault signaling module (2902958).

Fuse 2x 2.5 A Slow-blow (exchangeable)

Input voltage 24 V DC

Input voltage range 19.2 V DC ... 30 V DC

Input current ≤ 2 A

Redundant supply yes, decoupled from diodes

Polarization and surge protection Yes

Output name Switching output

Contact switching type 1 N/C contact (alarm = open)

Maximum switching voltage 30 V DC (2 A)

Connection data Power supply

Connection method Screw connection

Stripping length 7 mm

Number of connections 1

N...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TC-XC96-DO32-PS-P-HIMAX01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.