


INDUSTRIAL COMPONENT DATA

TDPT 2,5/ 9-SP-5,08 1017510 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: TDPT 2,5/ 9-SP-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	TDPT 2,5/ 9-SP-5,08
Catalog number	1017510
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-AE18948E85
Generated	2026-08-03

Product Overview

PCB terminal block

Terminal for printed circuit board, nominal current: 32 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of potentials: 9, number of rows: 1, number of poles per row: 9, family of articles: TDPT 2.5/.. -SP, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1017510

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626501444

Weight per Piece (excluding packing) 19.110 g

Custom tariff number 85369010

Country of origin CN (China)

Item properties

Brief article description PCB terminal block

Range of articles TDPT 2,5/..-SP

Pitch 5.08 mm

Number of positions 9

Connection method Push-in spring connection

Mounting type Wave soldering

Pin layout Linear double pinning

Number of levels 1

Electrical parameters

Rated current 32 A

Rated insulation voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Connection capacity

Conductor cross section solid 0.2 mm² ... 4 mm² (Conductor connection with open terminal point)

0.75 mm² ... 4 mm² (Push-in connection)

Conductor cross section flexible 0.2 mm² ... 4 mm²

Conductor cross section AWG / kcmil 24 ... 12

Conductor cross section flexible, with ferrule without plastic sleeve 0.2 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.2 mm² ... 2.5 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 0.75 mm²

Stripping length 10 mm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics Tin-plated

Metal surface terminal point (top layer) Tin (10 - 16 µm Sn)

Metal surface soldering area (top layer) Tin (10 - 16 µm Sn)

Material data - housing

Insula...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TDPT 2,5/ 9-SP-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.