

INDUSTRIAL COMPONENT DATA

TDPT 4/ 2-SC-6,35-ZB GY7035 1364959 PHOENIX CONTACT

Terminal block for printed circuit board, nominal curren..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TDPT 4/ 2-SC-6,35-ZB GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	TDPT 4/ 2-SC-6,35-ZB GY7035
Catalog number	1364959
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-1932690E94
Generated	2026-08-05

Product Overview

Terminal block for printed circuit board, nominal current: 41 A, nominal voltage (III/2): 1000 V, nominal section: 4 mm², number of rows: 1, number of poles per row: 2, article family: TDPT 4/.. -SC, pitch: 6.35 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: light gray, Pin arrangement: Zigzag pins W, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, Packing Type: Boxed Packed

Printed circuit board terminal, rated current: 41 A, sizing voltage (III/2): 1000 V, nominal section: 4 mm², number of rows: 1, number of poles per row: 2, item family: TDPT 4/.. -SC, pitch: 6.35 mm, connection type: Screw connection with traction capsule, screw clamping shape: L Longitudinal groove, mounting: Wave welding, connection direction conductor/printed circuit board: 0 °, color: light grey, Pin arrangement: Zigzag W pins, Pin length [P]: 3.5 mm, number of welding pins per potential: 1, type of packaging: packaged in box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

ETIM for 1364959 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

26.9 mm

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

6.35 mm

Rated current I_n (EF008250)

41 A

Rated voltage (EF000228)

1000 V

Rated surge voltage (EF002993)

8 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Screw connection

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.2 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section multi-wired (EF007343)

0.2 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.7 mm

Length pin (EF006825)

3.5 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Grey

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB fastening (EF008226)

Connecting contact

Type of fastening (EF002442)

Solder

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TDPT 4/ 2-SC-6,35-ZB GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.