


INDUSTRIAL COMPONENT DATA

ST 4-HESI (5X20) 3036369 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 4-HESI (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 4-HESI (5X20)
Catalog number	3036369
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-962F812C05
Generated	2026-08-03

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 500 V, nominal current: 6.3 A, connection type: Spring connection, Sizing cross-section: 4 mm², cross-section: 0.08 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, colour: black

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: G / 5 x 20, nom. voltage: 500 V, nominal current: 6.3 A, connection method: Spring-cage connection, Rated cross section: 4 mm², cross section: 0.08 mm²- 6 mm², mounting type: NS 35/7,5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Fuse terminal block

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 13

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Fuse type Glass / ceramics / ...

Rated surge voltage 6 kV

Maximum power dissipation for nominal condition 1.02 W

Fuse G / 5 x 20

Maximum power dissipation max. 1.6 W (with single arrangement of the fuse terminal block in the event of overload)

max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)

max. 4 W (with single arrangement of the fuse terminal block in the event of a short-circuit)

max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)

Connection data Number of connections per level 2

Nominal cross section 4 mm²

Level 1 above 1 below 1

Stripping length 8 mm ... 10 mm

Internal cylindrical gage A4

Connection in acc. with standard IEC 60947-7-3

Conductor cross section rigid 0.08 mm² ... 6 mm²

Cross section AWG 28 ... 10 (converted acc. to IEC)

Conductor cross section flexible 0.08 mm² ... 4 mm²

Conductor cross section, flexible [AWG] 28 ... 12 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 4 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 4 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 4-HESI (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.