


INDUSTRIAL COMPONENT DATA

UC1-TMF 8 GN CUS 0828352 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC1-TMF 8 GN CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC1-TMF 8 GN CUS
Catalog number	0828352
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-09DC99E19A
Generated	2026-08-03

Product Overview

Marker for terminal blocks

Marker for terminals, available: by mats, green, labeled according to customer specifications, mounting type: fit into flat index slot, for terminal width: 8.2 mm, usable surface: 7.65x5.2mm, Number of individual indexes: 64

Marker for terminal blocks, can be ordered: by sheet, green, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, Number of individual labels: 64

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Labeled terminal marker

Pitch 8.2 mm

Type flat

Data management status

Article revision 01

Marking

Number of individual labels 64

Number of individual labels per row 8

Identification technology UV LED technology

MountingMounting type snap into flat marker groove

Material specificationsRoHS compliant yes

Color green (RAL 6021)

Material PA

Flammability rating according to UL 94 V2

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 120 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 2

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 2

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 2

Components free from silicone and halogen

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Dimensions Width 8 mm

Pitch 8.2 mm

Standards and regulations Wipe resistance DIN EN 61010-1 (VDE 0411-1)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC1-TMF 8 GN CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.