

INDUSTRIAL COMPONENT DATA

UCT-TMF 12 VT CUS 0829690 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-TMF 12 VT CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-TMF 12 VT CUS
Catalog number	0829690
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-D3B08111A8
Generated	2026-07-28

Product Overview

Marker for terminal blocks

Marker for terminals, available: by mats, violet, labeled according to customer's instructions, mounting class: fit in groove for flat index, for terminal width: 12 mm, usable surface: 11.2 x 4.7 mm, Number of individual indices: 30

Marker for terminal blocks, can be ordered: by sheet, violet, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 12 mm, Number of individual labels: 30

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Labeled terminal marker

Pitch 12 mm

Type flat

Data management status

Article revision 01

Marking

Number of individual labels 30

Number of individual labels per row 5

Identification technology Thermal transfer for sheets and cards

MountingMounting type snap into flat marker groove

Material specificationsRoHS compliant yes

Color violet (RAL 4005)

Material PC

Flammability rating according to UL 94 V0

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Components free from silicone and halogen

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

Dimensions Width 11.45 mm

Height 1.64 mm

Length 5 mm

Pitch 12 mm

Standards and regulations Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Notes General Can be labeled via thermal transfer

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-TMF 12 VT CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.