


## INDUSTRIAL COMPONENT DATA

# UCT-TMF 4 VT CUS 0829655 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-TMF 4 VT CUS



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | PHOENIX CONTACT              |
| MPN / Reference | UCT-TMF 4 VT CUS             |
| Catalog number  | 0829655                      |
| Category        | Labelling for terminal block |
| Minimum order   | 1 Pcs                        |
| Document ID     | EO-5496E7D7A1                |
| Generated       | 2026-08-03                   |

## Product Overview

Marker for terminal blocks

Terminal marker, available: by mats, violet, labeled according to customer's instructions, mounting class: fit into flat index groove, for terminal width: 4.2 mm, usable surface: 3.4 x 4.7 mm, Number of individual indices: 90

Marker for terminals, available: by mats, purple, labelled according to customer specifications, mounting class: fit into flat index slot, for terminal width: 4.2 mm, Number of individual indexes: 90

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | PHOENIX CONTACT > CABINET add-on |
|--------------|----------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0829655

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 87 (C-5-2013)

GTIN 4046356598071

Weight per Piece (excluding packing) 9.200 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 5 mm

Width (a) 3.6 mm  
Height (c) 1.64 mm  
Ambient conditions  
Ambient temperature (operation) -40 °C ... 120 °C  
General  
Note Can be labeled via thermal transfer  
Color violet  
Type flat  
Components free from silicone and halogen  
Flammability rating according to UL 94 V0  
Material PC  
PC  
RoHS compliant Yes  
Wipe resistance DIN EN 61010-1 (VDE 0411-1)  
Number of individual labels 90  
Number of individual labels per row 15  
Printability Thermal transfer  
Inkjet printing  
Device 5146464 THERMOMARK CARD  
5146563 THERMOMARK CARD-UCT-MAG2  
5147888 BLUEMARK LED  
5147999 BLUEMARK CLED  
Ink ribbon 0801371 THERMOMARK-RIBBON 110-TC  
5147421 BLUEMARK FLUID-CARTRIDGE  
5146662 BLUEMARK CLED-FLUID-CARTR.  
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02  
Result Test passed  
Test specification weathering-resistance Following ISO 4892-2:2013-03  
Test duration 96 h  
Wipe resistance test result Test passed  
Salt spray test specification DIN EN 60068-2-11:2000-02  
Test duration 96 h  
Salt spray testing result Test passed  
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07  
Result Test passed  
Marking mounting type snap into flat marker groove  
Result Test passed  
Oxygen index (DIN EN ISO...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-TMF 4 VT CUS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.