

INDUSTRIAL COMPONENT DATA

UCT1-TMF 5 OG CUS 0829720 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT1-TMF 5 OG CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT1-TMF 5 OG CUS
Catalog number	0829720
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-6E484030C1
Generated	2026-08-03

Product Overview

Marker for terminal blocks

Terminal marker, available: by mats, orange, labeled according to customer's instructions, mounting class: fit in flat index groove, for terminal width: 5.2 mm, usable area: 4.45 x 5.2 mm, Number of individual indices: 72

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0829720

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 129 (C-5-2013)

GTIN 4046356598736

Weight per Piece (excluding packing) 10.670 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 5.2 mm

Width (a) 4.45 mm

Height (c) 2.36 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Note Can be labeled via thermal transfer

Color orange

Type flat

Components free from silicone and halogen

Flammability rating according to UL 94 V0

Material PC

PC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 72

Number of individual labels per row 12

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 min.

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type snap into flat marker groove

Result Test passed

Oxygen index (DIN EN ISO 4589-2) 32.4 %

R22 HL 1 - HL 3

R23 HL 1 - HL 3

R24 HL 1 - HL 3

Standards and Regulations

Wipe resistance DIN EN 61010-1 (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT1-TMF 5 OG CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.