

INDUSTRIAL COMPONENT DATA

DFK 4-SI(6,3X32) BK 0708344 PHOENIX CONTACT Fuse panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK 4-SI(6,3X32) BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK 4-SI(6,3X32) BK
Catalog number	0708344
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-874B95CBC1
Generated	2026-07-31

Product Overview

Fuse panel feed-through terminal block
Borne grommets, number of poles: 1, width: 12.2 mm, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 0708344
Packing unit 50 pc
Note Made to Order (non-returnable)
Catalog page Page 639 (C-1-2013)
GTIN 4017918004613
Weight per Piece (excluding packing) 16.480 g
Custom tariff number 85369010
Country of origin BG (Bulgaria)
General
Number of levels 1
Number of connections 2
Color black
Insulating material PA

Flammability rating according to UL 94 V2

Maximum load current 10 A

6.3 A

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-3

Nominal current I_N 10 A

Maximum load current 10 A

Nominal voltage U_N 400 V

Open side panel No

Number of positions 1

Dimensions

Width 12.2 mm

Length 51 mm

Pitch 6 mm

Plate thickness 1.5 mm

Connection data

Connection side Level 1 ext. 1

Connection method Screw connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, sol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK 4-SI(6,3X32) BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.