


INDUSTRIAL COMPONENT DATA

DIKD 1,5-LA 24RD/O-M 2715814 PHOENIX CONTACT

Sensor/actuator terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: DIKD 1,5-LA 24RD/O-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	DIKD 1,5-LA 24RD/O-M
Catalog number	2715814
Category	Sensor/actuator terminal block
Minimum order	50 Pcs
Document ID	EO-1D7E151EEC
Generated	2026-08-01

Product Overview

Sensor/actuator terminal block

Terminal block for detectors/actuators, nominal voltage: 250 V, nominal current: 24 A, connection type: Screw connection, 1., 2. and 3rd floor, Dimensioning cross-section: 2.5 mm², cross-section: 0.2 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 2715814

Packing unit 50 pc

Catalog page Page 445 (C-1-2017)

GTIN 4017918061562

Weight per Piece (excluding packing) 20.780 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 3

Number of connections 6

Nominal cross section 2.5 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Nominal current IN 24 A
Maximum load current 30 A (with 4 mm² conductor cross section)
Nominal voltage UN 250 V
Open side panel No
Dimensions
Width 6.2 mm
Length 72.5 mm
Height NS 35/7,5 54.5 mm
Height NS 35/15 62 mm
Connection data
Connection method Screw connection
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Cross section with insertion bridge, solid max. 4 mm²
Cross section wit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DIKD 1,5-LA 24RD/O-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.