

INDUSTRIAL COMPONENT DATA

IB IL 24 DI 32/HD-PAC 2862835 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL 24 DI 32/HD-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL 24 DI 32/HD-PAC
Catalog number	2862835
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-BFD58687E3
Generated	2026-08-01

Product Overview

Inline terminal

Inline, Digital input module, Digital inputs: 32, 24 VDC, connection technology: 1 conductor, transmission speed on the local bus:500 kBit/s, protection index: IP20, including inline connectors and marking fields

Inline, Digital Input Module, TOR Inputs: 32, 24 V DC, Connectors: 1-Wire, Local Bus Transmission Rate: 500 kBit/s, Protection Class: IP20, incl. Inline Male Connectors and Tracking Fields

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2862835

Packing unit 1 pc

Catalog page Page 147 (C-6-2017)

GTIN 4017918907594

Weight per Piece (excluding packing) 192.410 g

Custom tariff number 85389091

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 48.8 mm

Height 119.8 mm

Depth 71.5 mm

Note on dimensions Housing dimensions

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

80 kPa ... 106 kPa (up to 3000 m above sea level, in ATEX Zone 2)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 192.41 g

Note on weight specifications with connectors

Operating mode Process data operation with 2 words

Diagnostics messages No

Interfaces

Designation Inline local bus

No. of channels 2

Connection method Inline data jumper

Transmission speed 500 kbps

Inline potentials

Designation Communications power (UL)

Supply voltage 7.5 V DC (via voltage jumper)

Current consumption max. 90 mA

Power consumption max. 0.675 W

Designation Segment circuit supply (US)

Supply voltage 24 V DC (via voltage jumper)

Supply voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL 24 DI 32/HD-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.