

**INDUSTRIAL COMPONENT DATA**

# PT 1,5/S-QUATTRO RD 3208200 PHOENIX CONTACT

## Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/S-QUATTRO RD



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PT 1,5/S-QUATTRO RD         |
| Catalog number  | 3208200                     |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-73FC2C4BC8               |
| Generated       | 2026-08-03                  |

### Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 500 V, nominal current: 17.5 A, number of connections: 4, connection type: Push-in connection, 1st floor, Sizing cross-section: 1.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, color: red

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

### Additional Product Information

Key Commercial Data

Orderkey 3208200

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4046356680530

Weight per Piece (excluding packing) 5.310 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 4

Potentials 1

Nominal cross section 1.5 mm<sup>2</sup>

Color red

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.56 W

Maximum load current 17.5 A

Nominal current I<sub>N</sub> 17.5 A

Nominal voltage U<sub>N</sub> 500 V

Open side panel Yes

Dimensions

Width 3.5 mm

End cover width 2.2 mm

Length 63.2 mm

Height 30.5 mm

Height NS 35/7,5 32 mm

Height NS 35/15 39.5 mm

Connection data

Connection method Push-in connection

Stripping length 8 mm

Connection in acc. with standard IEC 60947-7-1

Conductor cross section solid min. 0.14 mm<sup>2</sup>

Conductor cross section solid max. 1.5 mm<sup>2</sup>

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

Conductor cross section flexible min. 0.14 mm<sup>2</sup>

Conductor cross section flexible max. 1.5 mm<sup>2</sup>

Min. AWG conductor cross section, flexible 26

Max. AWG conductor cross section, flexible 16

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.14 mm<sup>2</sup>

Conductor cross section flex...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/S-QUATTRO RD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.