


INDUSTRIAL COMPONENT DATA

PT 1,5/S-TWIN/1P-PE 3212374 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/S-TWIN/1P-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/S-TWIN/1P-PE
Catalog number	3212374
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-98CEA6016A
Generated	2026-08-01

Product Overview

Ground modular terminal block

Ground terminal, number of connections: 3, connection type: Push-in connection / plug-in connection, 1st floor, cross-section: 0.14 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, colour: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3212374

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 279 (C-1-2017)

GTIN 4046356641333

Weight per Piece (excluding packing) 5.990 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 3

Nominal cross section 1.5 mm²

Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum load current 17.5 A (with 1.5 mm² conductor cross section)
Open side panel Yes
Insertion/withdrawal cycles mechanical 100
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f₁= 5 Hz to f₂= 150 Hz
ASD level 1.857 (m/s²)²/Hz
Acceleration 0,8 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 5 g
Shock duration 30 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/S-TWIN/1P-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.