

INDUSTRIAL COMPONENT DATA

PT 2,5-TWIN-MT BU 3211663 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-TWIN-MT BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-TWIN-MT BU
Catalog number	3211663
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-8086C8AEE4
Generated	2026-08-01

Product Overview

Knife disconnect terminal block

Blade interruptible terminal block, nominal voltage: 400 V, nominal current: 20 A, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, colour: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3211663

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 77 (C-1-2017)

GTIN 4046356446518

Weight per Piece (excluding packing) 10.930 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 3

Nominal cross section 2.5 mm²

Color blue
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W
Maximum load current 20 A (with 4 mm² conductor cross section)
Nominal current IN 20 A
Nominal voltage UN 400 V
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-TWIN-MT BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.