


INDUSTRIAL COMPONENT DATA

PT 4-QUATTRO BU 3211802 PHOENIX CONTACT

Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 4-QUATTRO BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 4-QUATTRO BU
Catalog number	3211802
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-F5223C0530
Generated	2026-08-03

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 800 V, nominal current: 32 A, number of connections: 4, connection type: Push-in connection, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: blue

Feed-through terminal block, nom. voltage: 800 V, nominal current: 32 A, number of connections: 4, connection method: Push-in connection, Rated cross section: 4 mm², cross section: 0.2 mm² - 6 mm², mounting type: NS 35/7,5, NS 35/15, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Multi-conductor terminal block

Area of application Railway industry

Machine building

Plant engineering

Process industry

Number of connections 4

Number of rows 1

Potentials 1

Data management status

Article revision 16

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 8 kV

Maximum power dissipation for nominal condition 1.02 W

Connection data Number of connections per level 4

Nominal cross section 4 mm²

Stripping length 10 mm ... 12 mm

Internal cylindrical gage A4

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 0.2 mm² ... 6 mm²

Cross section AWG 24 ... 10 (converted acc. to IEC)

Conductor cross section flexible 0.2 mm² ... 6 mm²

Conductor cross section, flexible [AWG] 24 ... 10 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²

Nominal current 32 A

Maximum load current 36 A (with 6 mm² conductor cross section, rigid)

Nominal voltage 800 V

Nominal cross section 4 mm²

Connection cross sections directly pluggable

Conductor cross section rigid 0.5 mm² ... 6 mm²

Conductor cross-section flexible (ferrule without plastic sleeve) 0.75 mm² ... 4 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.75 mm² ... 4 mm²

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 4-QUATTRO BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.