


INDUSTRIAL COMPONENT DATA

PTB 2,5-PE/L/L 3210547 PHOENIX CONTACT Installation ground terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTB 2,5-PE/L/L



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTB 2,5-PE/L/L
Catalog number	3210547
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-629ED4448F
Generated	2026-08-01

Product Overview

Installation ground terminal block

Ground terminal block for distribution, nominal voltage: 400 V, nominal current: 20 A, Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3210547

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 90 (C-1-2017)

GTIN 4046356701334

Weight per Piece (excluding packing) 21.940 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 3

Number of connections 5

Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Nominal current I_N 20 A (with a 2.5 mm² conductor cross section)
Maximum load current 24 A (with 4 mm² conductor cross section and 3-pos. terminal block)
Nominal voltage U_N 400 V (phase conductor/phase conductor)
250 V (phase conductor/PE)
Nominal current I_N(upper level) 16 A (with a 2.5 mm² conductor cross section)
Maximum load current (upper level) 16 A (with 4 mm² conductor cross section)
Nominal voltage U_N 250 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Checking the mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTB 2,5-PE/L/L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.