


INDUSTRIAL COMPONENT DATA

PTB 2,5-PE/L/TG 3210539 PHOENIX CONTACT Installation ground terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTB 2,5-PE/L/TG



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTB 2,5-PE/L/TG
Catalog number	3210539
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-F41A0058ED
Generated	2026-08-03

Product Overview

Installation ground terminal block

Ground terminal for distribution, Current and voltage are determined by the connector used., nominal voltage: 400 V, nominal current: 22 A, Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3210539

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 89 (C-1-2017)

GTIN 4046356693769

Weight per Piece (excluding packing) 21.400 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 3

Number of connections 5
Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Nominal current I_N 22 A (with a 2.5 mm² conductor cross section)
Maximum load current 24 A (with 4 mm² conductor cross section)
28 A (with 4 mm² conductor cross section and 3-pos. terminal block)
Nominal voltage U_N 400 V (phase conductor/phase conductor)
250 V (phase conductor/PE)
Nominal current I_N(upper level) 16 A (with a 2.5 mm² conductor cross section)
Maximum load current (upper level) 16 A (with 4 mm² conductor cross section)
16 A (with 1.5 mm² conductor cross section and 3-pos. terminal block base)
Nominal voltage U_N 250 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Ch...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTB 2,5-PE/L/TG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.