


INDUSTRIAL COMPONENT DATA

PTI 2,5-L/TG 3213961 PHOENIX CONTACT Installation level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTI 2,5-L/TG



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTI 2,5-L/TG
Catalog number	3213961
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-A4FC4C7507
Generated	2026-08-01

Product Overview

Installation level terminal block

Terminal block of distribution floor, Current and voltage are determined by the connector used., nominal voltage: 400 V, nominal current: 24 A, Push-in connection, Dimensioning cross-section: 4 mm², cross-section: 0.14 mm² - 4 mm², Push-in connection, Dimensioning cross-section: 1.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3213961

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 75 (C-1-2017)

GTIN 4046356609531

Weight per Piece (excluding packing) 15.640 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 3

Number of connections 4
Potentials 2
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Maximum load current 30 A (with 4 mm² conductor cross section and 3-pos. terminal block)
16 A (disconnect level 16 A. The current is determined by the component used.)
Rated surge voltage 4 kV
6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)
Maximum load current 30 A (with 4 mm² conductor cross section and 3-pos. terminal block)
Nominal current I_N 24 A (with 4 mm² conductor cross section)
Nominal voltage U_N 400 V (phase conductor/phase conductor)
250 V (phase conductor/PE)
phase conductor/N
Maximum load current 16 A (with 4 mm² conductor cross section)
Nominal current I_N 16 A
Nominal voltage U_N 250 V
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTI 2,5-L/TG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.