

INDUSTRIAL COMPONENT DATA

PTTB 1,5/S/4P-PE 3213881 PHOENIX CONTACT Protective conductor double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTB 1,5/S/4P-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTTB 1,5/S/4P-PE
Catalog number	3213881
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-3B5A437F20
Generated	2026-08-01

Product Overview

Protective conductor double-level terminal block

Double-deck terminal block with protective conductor, number of connections: 4, connection type: Plug-in connection, 1st and 2nd level, cross-section: 0.14 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, color: yellow-green

Double-deck terminal block for earth conductors, number of connections: 4, connection type: Connector connection, 1. and 2. top, cross-section: 0.14 mm² - 1.5 mm², mounting type: NS 35/7.5, NS 35/15, colour: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3213881

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 280 (C-1-2017)

GTIN 4046356575683

Weight per Piece (excluding packing) 8.410 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2
Number of connections 4
Nominal cross section 1.5 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 61984
Open side panel Yes
Insertion/withdrawal cycles mechanical 100
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f₁= 5 Hz to f₂= 150 Hz
ASD level 1.857 (m/s²)²/Hz
Acceleration 0,8 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 5 g
Shock duration 30 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Relative insulation material temperature index (Elec.; UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTB 1,5/S/4P-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.