

**INDUSTRIAL COMPONENT DATA**

# PTTBS 1,5/S/2P-PV 3214521 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTBS 1,5/S/2P-PV



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | PTTBS 1,5/S/2P-PV           |
| Catalog number  | 3214521                     |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-CF0D002F6E               |
| Generated       | 2026-07-29                  |

## Product Overview

Double-level terminal block

Double-level terminal, The current and voltage are determined by the connector used., with potential splicers, nominal voltage: 500 V, nominal current: 16 A, connection type: Push-in connection / plug-in connection, 1st and 2nd floor, Dimensioning section: 1.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, color: grey

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3214521

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 281 (C-1-2017)

GTIN 4046356623353

Weight per Piece (excluding packing) 7.600 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 4  
Nominal cross section 1.5 mm<sup>2</sup>  
Color gray  
Insulating material PA  
Flammability rating according to UL 94 V0  
Rated surge voltage 6 kV  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)  
Connection in acc. with standard IEC 61984  
Nominal current I<sub>N</sub> 16 A (observe derating)  
Maximum load current 16 A (with 1.5 mm<sup>2</sup> conductor cross section)  
Nominal voltage U<sub>N</sub> 500 V  
Open side panel Yes  
Insertion/withdrawal cycles mechanical 100  
Result of surge voltage test Test passed  
Surge voltage test setpoint 7.3 kV  
Result of tight fit on support Test passed  
Tight fit on carrier NS 35  
Setpoint 1 N  
Short circuit stability result Test passed  
Conductor cross section short circuit testing 1.5 mm<sup>2</sup>  
Short-time current 0.18 kA  
Result of thermal test Test passed  
Proof of thermal characteristics (needle flame) effective duration 30 s  
Oscillation, broadband noise test result Test passed  
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03  
Test spectrum Service life test category 1, class B, body mounted  
Test frequency f<sub>1</sub>= 5 Hz to f<sub>2</sub>= 150 Hz  
AS...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTBS 1,5/S/2P-PV with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.