

INDUSTRIAL COMPONENT DATA

SLKK 5-LA 60 RD/U-O 0461034 PHOENIX CONTACT

Component terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SLKK 5-LA 60 RD/U-O



Manufacturer	PHOENIX CONTACT
MPN / Reference	SLKK 5-LA 60 RD/U-O
Catalog number	0461034
Category	Component terminal block
Minimum order	50 Pcs
Document ID	EO-DE6870FE90
Generated	2026-08-02

Product Overview

Component terminal block

Terminal block for components, nominal voltage: 500 V, nominal current: 34 A, 1st floor, connection type: Screw connection, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0461034

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 450 (C-1-2017)

GTIN 4017918002404

Weight per Piece (excluding packing) 22.020 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 3

Number of connections 5

Nominal cross section 4 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 34 A
Maximum load current 34 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V (Data is based on the dielectric strength of adjacent terminal blocks or of the DINg rail.)
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail ve...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SLKK 5-LA 60 RD/U-O with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.