


INDUSTRIAL COMPONENT DATA

ST 1,5-QUATTRO-U 3038600 PHOENIX CONTACT

Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 1,5-QUATTRO-U



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 1,5-QUATTRO-U
Catalog number	3038600
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-F26348F77D
Generated	2026-08-01

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 500 V, nominal current: 17.5 A, number of connections: 4, connection type: Spring connection, 1st floor, Dimensioning cross-section: 1.5 mm², cross-section: 0.08 mm² - 1.5 mm², installation class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3038600

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 153 (C-1-2017)

GTIN 4017918891220

Weight per Piece (excluding packing) 7.600 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 1.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.56 W

Maximum load current 17.5 A (in case of a 1.5 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)

Nominal current I_N 17.5 A (with 1.5 mm² conductor cross section)

Nominal voltage U_N 500 V

Open side panel Yes

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 7.3 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.89 kV

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.08 mm² / 0.1 kg

1.5 mm² / 0.4 kg

Tensile test result Test passed

Conductor cross....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 1,5-QUATTRO-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.