

INDUSTRIAL COMPONENT DATA

ST 4-FSI/C-LED 12 3036495 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 4-FSI/C-LED 12



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 4-FSI/C-LED 12
Catalog number	3036495
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-C05B743324
Generated	2026-08-04

Product Overview

Fuse modular terminal block

Fuse terminal block with light indication, for installation on NS 35, for circuit breakers, terminal width: 8.2 mm, color: Black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3036495

Packing unit 50 pc

Catalog page Page 177 (C-1-2017)

GTIN 4017918890452

Weight per Piece (excluding packing) 21.130 g

Custom tariff number 85369095

Country of origin TR (Turkey)

General

Number of levels 1

Number of connections 2

Mounting type NS 35/7,5

Color black

Insulating material PA

Flammability rating according to UL 94 V0

Electrical data

Fuse C

Fuse type Flat

Degree of pollution 3

Insulating material group I

Connection in acc. with standard IEC 60947-7-3

Maximum current with single arrangement 30 A

Voltage LED 12 V DC

Current LED 2 mA

Dimensions

Width 8.2 mm

Height NS 35/7,5 43.5 mm

Height NS 35/15 51 mm

Connection data

Conductor cross section solid min. 0.08 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section flexible min. 0.08 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section AWG min. 28

Conductor cross section AWG max. 10

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.14 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 1 mm²

Connection method Spring-cage connection

Internal cylindrical gage....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 4-FSI/C-LED 12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.