

INDUSTRIAL COMPONENT DATA

ST 4-FSI/C-LED 48 3035250 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 4-FSI/C-LED 48



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 4-FSI/C-LED 48
Catalog number	3035250
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-10D219FE67
Generated	2026-08-01

Product Overview

Fuse modular terminal block

Fuse terminal block with light indication, for installation on NS 35, for circuit breakers, terminal width: 8.2 mm, color: Black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3035250

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 184 (CL1-2011)

GTIN 4046356053594

Weight per Piece (excluding packing) 21.350 g

Custom tariff number 85369095

Country of origin TR (Turkey)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 1.02 W
Fuse C
Fuse type Flat
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum current with single arrangement 30 A
Voltage LED 48 V DC
Current LED 2 mA
Connection in acc. with standard IEC 60947-7-3
Maximum load current 30 A
Nominal current IN 30 A
Nominal voltage UN 48 V
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 4-FSI/C-LED 48 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.