

INDUSTRIAL COMPONENT DATA

STIO 2,5/4-3B/L 3209057 PHOENIX CONTACT Sensor/actuator terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: STIO 2,5/4-3B/L



Manufacturer	PHOENIX CONTACT
MPN / Reference	STIO 2,5/4-3B/L
Catalog number	3209057
Category	Sensor/actuator terminal block
Minimum order	50 Pcs
Document ID	EO-A04C7EBA0A
Generated	2026-08-03

Product Overview

Sensor/actuator terminal block

Terminal block for detectors/actuators, nominal voltage: 250 V, nominal current: 18 A, number of connections: 5, connection type: Spring connection, Dimension cross-section: 2.5 mm², cross-section: 0.08 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

Actuator/proximity sensor terminal block, nominal voltage: 250 V, nominal current: 18 A, number of connections: 5, connection type: Spring connection, Sizing cross-section: 2.5 mm², cross-section: 0.08 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 3209057

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 161 (C-1-2017)

GTIN 4046356143301

Weight per Piece (excluding packing) 11.120 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 3

Number of connections 5

Nominal cross section 2.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)

Connection in acc. with standard IEC 60947-7-1

Nominal current I_N 18 AMaximum load current 18 A (with 4 mm² conductor cross section)Nominal voltage U_N 250 V

Open side panel Yes

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 4.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.5 kV

Checking the mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.08 mm² / 0.1 kg2.5 mm² / 0.7 kg4 mm² / 0.9 kg

Tensile test result Test passed

Conductor cross section tensile test 0.08 mm²

Tractive force setpoint...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STIO 2,5/4-3B/L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.