


INDUSTRIAL COMPONENT DATA

STIO 2,5/4-PE/2B/L 3209060 PHOENIX CONTACT Installation ground terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: STIO 2,5/4-PE/2B/L



Manufacturer	PHOENIX CONTACT
MPN / Reference	STIO 2,5/4-PE/2B/L
Catalog number	3209060
Category	Sensor/actuator terminal block
Minimum order	50 Pcs
Document ID	EO-AC03F437F0
Generated	2026-07-29

Product Overview

Installation ground terminal block

Ground terminal for distribution, nominal voltage: 250 V, nominal current: 18 A, number of connections: 5, connection type: Spring connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.08 mm² - 4 mm², installation class: NS 35/7.5, NS 35/15, colour: grey

Installation ground terminal block, nom. voltage: 250 V, nominal current: 18 A, number of connections: 5, connection method: Spring-cage connection, Rated cross section: 2.5 mm², cross section: 0.08 mm² - 4 mm², mounting type: NS 35/7,5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator terminal block

Number of connections 5

Number of rows 3

Data management status

Article revision 01

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 4 kV

Maximum power dissipation for nominal condition 0.77 W
Connection dataGrounding foot Yes
Number of connections per level 5
Nominal cross section 2.5 mm²
Note Please observe the current carrying capacity of the DIN rails.
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A3
Connection in acc. with standard IEC 60947-7-1/IEC 60947-7-2
Conductor cross section rigid 0.08 mm² ... 4 mm²
Cross section AWG 28 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.08 mm² ... 2.5 mm²
Conductor cross section, flexible [AWG] 28 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 2.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm²
Nominal current 18 A
Maximum load current 18 A (with 4 mm² conductor cross section)
Nominal voltage 250 V
Nominal cross section 2.5 mm²
DimensionsWidth 5.2 mm
End cover width 2.2 mm
Height 92.3 mm
Depth on NS 35/7,5 44.5 mm
Depth on NS 35/15 52 mm
Material specificationsColor gray (RAL 7042)
Flammability rating according to UL 94 V0
Insulating material group I
Insulating mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STIO 2,5/4-PE/2B/L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.