

INDUSTRIAL COMPONENT DATA

UDK 3 2775375 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UDK 3



Manufacturer	PHOENIX CONTACT
MPN / Reference	UDK 3
Catalog number	2775375
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-3B24E72BC5
Generated	2026-08-02

Product Overview

Feed-through terminal block

1-story terminal block with double connection on both sides, cross-section: 0.2 - 2.5 mm², AWG: 30 - 12, width: 5.2 mm, colour: Grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 2775375

Packing unit 50 pc

Catalog page Page 432 (C-1-2017)

GTIN 4017918068578

Weight per Piece (excluding packing) 11.580 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 2

Number of connections 4

Potentials 1

Nominal cross section 2.5 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Maximum load current 32 A (in case of a 4 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)
Nominal current IN 24 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel Yes
Shock protection test specification IEC 60529:2001-02
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.2 mm² / 0.2 kg
2.5 mm² / 0.7 kg
4 mm² / 0.9 kg
Tensile test result Test passed...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UDK 3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.