


## INDUSTRIAL COMPONENT DATA

# UK 5-HESILED 24 N 3000540 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 5-HESILED 24 N



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | UK 5-HESILED 24 N   |
| Catalog number  | 3000540             |
| Category        | Fuse terminal block |
| Minimum order   | 50 Pcs              |
| Document ID     | EO-1BB662DFD2       |
| Generated       | 2026-08-03          |

## Product Overview

Fuse modular terminal block

Fuse rail terminal, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 24 V, nominal current: 6.3 A, number of poles: 1, connection type: Screw connection, Sizing cross-section: 1.5 mm<sup>2</sup>, cross-section: 0.2 mm<sup>2</sup>- 6 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, NS 32, color: black

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3000540

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 452 (C-1-2017)

GTIN 4046356676038

Weight per Piece (excluding packing) 14.350 g

Custom tariff number 85369095

Country of origin CN (China)

General

Note For terminal marking, please use marking material with 8.2 mm pitch.

For lever marking, please use marking material with 6.2 mm pitch.

Number of levels 1  
Number of connections 2  
Nominal cross section 4 mm<sup>2</sup>  
Color black  
Insulating material PA  
Flammability rating according to UL 94 V0  
Maximum power dissipation for nominal condition 1.6 W  
Fuse G / 5 x 20  
Fuse type Glass / ceramics / ...  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)  
max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)  
max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)  
max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)  
LED voltage range 12 V AC/DC ... 30 V AC/DC  
LED current range 0.7 mA ... 1.95 mA  
Connection in acc. with standard IEC 60947-7-3  
Maximum load current 6.3 A (the current is determined by the fuse used)  
Nominal current I<sub>N</sub> 6.3 A  
Nominal voltage U<sub>N</sub> 24 V  
Open side panel Yes  
Number of positions 1  
Relative insulation material temperature index....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 5-HESILED 24 N with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.