


INDUSTRIAL COMPONENT DATA

UT 4-QUATTRO HV RD 3048849 PHOENIX CONTACT

Four-conductor universal terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-QUATTRO HV RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-QUATTRO HV RD
Catalog number	3048849
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-BBA272E102
Generated	2026-07-29

Product Overview

Four-conductor universal terminal block

Four-conductor universal terminal block, nominal voltage: 1000 V, nominal current: 32 A, number of connections: 4, connection type: Screw connection, 1st floor, Sizing cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3048849

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 55 (NTK-2012)

GTIN 4046356517584

Weight per Piece (excluding packing) 16.710 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 4

Potentials 1

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W

Maximum load current 37 A (In the case of a 6 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors)

Nominal current I_N 32 A

Nominal voltage U_N 1000 V

Open side panel Yes

Dimensions

Width 6.2 mm

End cover width 2.2 mm

Length 65.4 mm

Height NS 35/7,5 50 mm

Height NS 35/15 57.5 mm

Connection data

Connection method Screw connection

Screw thread M3

Stripping length 9 mm

Tightening torque, min 0.6 Nm

Tightening torque max 0.8 Nm

Connection in acc. with standard IEC 60947-7-1

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 10

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 6 mm²

Min. AWG conductor cross section, flexible 26

Max. AWG conductor cross section, flexible 10

Conductor cros...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-QUATTRO HV RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.