

INDUSTRIAL COMPONENT DATA

UT 4-QUATTRO-TG P/P BU 3073089 PHOENIX CONTACT

Disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-QUATTRO-TG P/P BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-QUATTRO-TG P/P BU
Catalog number	3073089
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-0B5A96394B
Generated	2026-08-05

Product Overview

Disconnect terminal block

Interruptible terminal block, The maximum load current must not be exceeded by the sum current of all connected conductors. The current and voltage are determined by the connector used., with threaded socket sockets to house test pins, rated voltage: 500 V, rated current: 20 A, connection type: Screw connection, Sizing section: 2.5 mm², cross-section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3073089

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 234 (C-1-2017)

GTIN 4046356333962

Weight per Piece (excluding packing) 17.620 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note The max. load current must not be exceeded by the total current of all connected conductors. Current and voltage are determined by the plug used.

Number of levels 1

Number of connections 4

Nominal cross section 4 mm²

Color blue

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W

Maximum load current 20 A (with 6 mm² conductor cross section)

Nominal current I_N 20 A (with 6 mm² conductor cross section)

Nominal voltage U_N 500 V

Open side panel Yes

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat re...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-QUATTRO-TG P/P BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.