

INDUSTRIAL COMPONENT DATA

UTI 35-PE 3074091 PHOENIX CONTACT Installation ground terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTI 35-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTI 35-PE
Catalog number	3074091
Category	Multi level installation terminal block
Minimum order	1 Pcs
Document ID	EO-58CBBE36FB
Generated	2026-07-29

Product Overview

Installation ground terminal block

Ground terminal block for distribution, Screw connection, Sizing cross-section: 35 mm², cross-section: 0.75 mm² - 35 mm², installation class: NS 35/7.5, NS 35/15, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3074091

Packing unit 50 pc

Catalog page Page 255 (C-1-2017)

GTIN 4046356347273

Weight per Piece (excluding packing) 67.110 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 2

Potentials 2

Nominal cross section 35 mm²

Color green-yellow

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Nominal current I_N 125 A

Nominal voltage U_N 800 V

Open side panel No

Terminal block mounting 2.5 Nm ... 3 Nm (PE foot with mounting screw, M5)

Dimensions

Width 15 mm

Length 55 mm

Height NS 35/7,5 51 mm

Height NS 35/15 58.5 mm

Connection data

Note Please observe the current carrying capacity of the DIN rails.

Connection method Screw connection

Screw thread M6

Stripping length 16 mm

Tightening torque, min 3.2 Nm

Tightening torque max 3.7 Nm

Connection in acc. with standard IEC 60947-7-2

Conductor cross section solid min. 0.75 mm²

Conductor cross section solid max. 35 mm²

Conductor cross section AWG min. 18

Conductor cross section AWG max. 2

Conductor cross section flexible min. 0.75 mm²

Conductor cross section flexible max. 35 mm²

Min. AWG conductor cross section, flexible 18

Max. AWG conductor cross section, flexible 2

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.75 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 35 mm²

Conductor cro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTI 35-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.