

INDUSTRIAL COMPONENT DATA

UTTB 4-MT P/P LA 24 RD/O-U 3046773 PHOENIX CONTACT

Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTTB 4-MT P/P LA 24 RD/O-U



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTTB 4-MT P/P LA 24 RD/O-U
Catalog number	3046773
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-344CD6A460
Generated	2026-08-02

Product Overview

Knife disconnect terminal block

Blade interruptible terminal block, with threaded sockets for test sockets to accommodate test pins, nominal voltage: 24 V, nominal current: 30 A, connection type: Screw connection, Sizing section: 4 mm², section: 0.14 mm² - 6 mm², connection type: Screw connection, Sizing section: 4 mm², section: 0.14 mm² - 6 mm², Mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3046773

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 237 (C-1-2017)

GTIN 4046356105675

Weight per Piece (excluding packing) 21.890 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 4

Potentials 1

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)

Maximum load current 38 A (with 6 mm² conductor cross section)

Nominal current IN 30 A

Nominal voltage UN 24 V

Maximum load current 20 A (with 6 mm² conductor cross section)

Nominal current IN 20 A

Nominal voltage UN 24 V

Open side panel Yes

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 4.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.5 kV

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.14 mm² / 0.2 kg

4 mm² / 0.9 kg

6 mm² / 1.4 kg

Tensile test....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 4-MT P/P LA 24 RD/O-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.