

**INDUSTRIAL COMPONENT DATA**

# **UTTB 4-MT P/P LA 24 RD/O-U 3046773 PHOENIX CONTACT** **Knife disconnect terminal block**

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTTB 4-MT P/P LA 24 RD/O-U



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | UTTB 4-MT P/P LA 24 RD/O-U        |
| Catalog number  | 3046773                           |
| Category        | (Knife) disconnect terminal block |
| Minimum order   | 50 Pcs                            |
| Document ID     | EO-344CD6A460                     |
| Generated       | 2026-08-04                        |

## **Product Overview**

Knife disconnect terminal block

Blade interruptible terminal block, with threaded sockets for test sockets to accommodate test pins, nominal voltage: 24 V, nominal current: 30 A, connection type: Screw connection, Sizing section: 4 mm<sup>2</sup>, section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, connection type: Screw connection, Sizing section: 4 mm<sup>2</sup>, section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, Mounting: NS 35/7.5, NS 35/15, color: gray

**STRUCTURED PRODUCT DATA**

## **Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

## **Classification & Catalog Path**

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## **Additional Product Information**

Key Commercial Data

Orderkey 3046773

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 237 (C-1-2017)

GTIN 4046356105675

Weight per Piece (excluding packing) 21.890 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 4

**Potentials 1**Nominal cross section 4 mm<sup>2</sup>

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)

Maximum load current 38 A (with 6 mm<sup>2</sup> conductor cross section)

Nominal current IN 30 A

Nominal voltage UN 24 V

Maximum load current 20 A (with 6 mm<sup>2</sup> conductor cross section)

Nominal current IN 20 A

Nominal voltage UN 24 V

Open side panel Yes

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 4.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.5 kV

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.14 mm<sup>2</sup> / 0.2 kg4 mm<sup>2</sup> / 0.9 kg6 mm<sup>2</sup> / 1.4 kg

Tensile test....

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / UTTB 4-MT P/P LA 24 RD/O-U with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.