

INDUSTRIAL COMPONENT DATA

E S6 A 400X200X120 0899013 PHOENIX CONTACT Junction box

Brand: PHOENIX CONTACT | Manufacturer Part Number: E S6 A 400X200X120



Manufacturer	PHOENIX CONTACT
MPN / Reference	E S6 A 400X200X120
Catalog number	0899013
Category	Enclosure/switchgear cabinet (empty)
Minimum order	2 Pcs
Document ID	EO-9E22AC0CE6
Generated	2026-08-05

Product Overview

Junction box

Empty housing, material: 316L / 1.4404 sterling steel, surface resistance: brushed, silver, 400 mm x 200 mm x 120 mm, closure type: Screw cap, delivery volume - ATD: Mounting plate, Fixing square with mounting screws, M12 grounding bolt placed on the outside, Installation instructions, Mounting plate

Empty enclosure, material: Stainless steel, 316L/1.4404, surface resistance: brushed, silver, 400 mm x 200 mm x 120 mm, type of locking: Screw-on cover, scope of supply - ATD: Mounting panel, Fixing angle with mounting screws, M12 grounding bolts, affixed externally, Installation notes, Mounting panel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Terminal box

Scope of delivery Mounting panel

Fixing angle with mounting screws

M12 grounding bolts, affixed externally

Installation notes

Type 20

Data management status

Article revision 01

Insulation characteristics

Protection class I**Electrical properties**Maximum power dissipation 13.4 W (T6 up to 40 °C)

8.3 W (T6 up to 55 °C)

5 W (T6 up to 65 °C)

18.4 W (T5 up to 40 °C)

13.4 W (T5 up to 55 °C)

10.1 W (T5 up to 65 °C)

21.8 W (T4 up to 40 °C)

10.5 W (T4 up to 55 °C)

13.4 W (T4 up to 65 °C)

DimensionsDimensional drawing

Width 400 mm

Height 200 mm

Depth 120 mm

Clearance width, maximum DIN rail length 344 mm

Max. material thickness 1.5 mm

Material specificationsColor silver

Material Stainless steel, 316L/1.4404

Seal material Silicon

Surface characteristics brushed

Note 240 grain

Mechanical propertiesGeneral

Type of locking (GRP) Screw-on cover Allen screws

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -55 °C ... 135 °C

MountingAssembly note External fixing clips

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend PHOENIX CONTACT / E S6 A 400X200X120 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.