

INDUSTRIAL COMPONENT DATA

C S6 A 382X458X210 0899096 PHOENIX CONTACT Junction box

Brand: PHOENIX CONTACT | Manufacturer Part Number: C S6 A 382X458X210



Manufacturer	PHOENIX CONTACT
MPN / Reference	C S6 A 382X458X210
Catalog number	0899096
Category	Enclosure/switchgear cabinet (empty)
Minimum order	2 Pcs
Document ID	EO-9EF2AAAAEC
Generated	2026-08-04

Product Overview

Junction box

Empty housing, material: Sterling steel 316L / 1.4404, surface resistance: brushed, silver, 382 mm x 458 mm x 210 mm, type of closure: Door with changeable hinge, delivery volume - ATD: Door hinge with quarter turn swivel closure, Mounting plate, Double bit key, Mounting bracket with mounting screws, M12 Grounding Bolt Placed Outside, Installation Instructions, Door Hinge with Twist Lock with Quarter Turn

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 0899096

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 530 (C-3-2017)

GTIN 4046356928588

Weight per Piece (excluding packing) 10,410.000 g

Custom tariff number 94032080

Country of origin DE (Germany)

General

Scope of supply Door hinge with quarter turn locking

Mounting plate

Double-bit key

Fixing angle with mounting screws

M12 grounding bolts, affixed externally

Installation notes

Color silver

Dimensions

Width 382 mm

Height 458 mm

Depth 210 mm

Clearance width, maximum DIN rail length 652 mm

Max. material thickness 1.5 mm

General

Housing material Stainless steel, 316L/1.4404

Surface characteristics brushed

Note 240 grain

Cover fastening Door with replaceable hinge

Note Quarter turn locking with two-way key bit

Fixing device External fixing clips

Seal material Silicon

Ambient conditions

Degree of protection of housing (IP) IP66

Protection class I

Degree of protection (IK) 7.00 J

Temperature in operating conditions -55 °C ... 135 °C

Classifications

eCl@ss 10.0.127180190eCl@ss 4.027180101eCl@ss 4.127180101eCl@ss 5.027180502eCl@ss 5.127180100eCl@ss
6.027180100eCl@ss 7.027180190eCl@ss 8.027180190eCl@ss 9.027180190

ETIM 4.0EC000261ETIM 5.0EC000261ETIM 6.0EC000261

UNSPSC 13.231261502

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C S6 A 382X458X210 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.