

INDUSTRIAL COMPONENT DATA

C3 S6 A 382X458X210 0899098 PHOENIX CONTACT Junction box

Brand: PHOENIX CONTACT | Manufacturer Part Number: C3 S6 A 382X458X210



Manufacturer	PHOENIX CONTACT
MPN / Reference	C3 S6 A 382X458X210
Catalog number	0899098
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-0626D91300
Generated	2026-08-05

Product Overview

Junction box

Terminal box, equipped with flange plates at the bottom left and right, material: Sterling steel 316L / 1.4404, surface resistance: brushed, silver, 382 mm x 458 mm x 210 mm, type of closure: Door with changeable hinge, scope of delivery - ATD: Door hinge with quarter turn swivel lock, Mounting plate, Double Bit Wrench, Mounting Bracket with Mounting Screws, M12 Grounding Bolt Placed on the Outside, Installation Instructions, Door Hinge with Quarter Turn Twist Lock

Junction box, With flange plate fixing, below, left and right, material: Stainless steel, 316L/1.4404, surface resistance: brushed, silver, 382 mm x 458 mm x 210 mm, type of locking: Door with replaceable hinge, scope of supply - ATD: Door hinge with quarter turn locking, Mounting panel, Double-bit key, Fixing angle with mounting screws, M12 grounding bolts, affixed externally, Installation notes, Door hinge with quarter turn locking

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Technical dataProduct propertiesProduct type Terminal box

Scope of delivery Door hinge with quarter turn locking

Mounting panel

Double-bit key

Fixing angle with mounting screws

M12 grounding bolts, affixed externally

Installation notes

Type 31

Data management status

Article revision 00

Insulation characteristics

Protection class I

Electrical propertiesMaximum power dissipation 24 W (T6 up to 40 °C)

15 W (T6 up to 55 °C)

9 W (T6 up to 65 °C)

33 W (T5 up to 40 °C)

24 W (T5 up to 55 °C)

18 W (T5 up to 65 °C)

39 W (T4 up to 40 °C)

18.8 W (T4 up to 55 °C)

24 W (T4 up to 65 °C)

DimensionsDimensional drawing

Width 382 mm

Height 458 mm

Depth 210 mm

Clearance width, maximum DIN rail length 652 mm

Max. material thickness 1.5 mm

Material specificationsColor silver

Material Stainless steel, 316L/1.4404

Seal material Silicon

Surface characteristics brushed

Note 240 grain

Mechanical propertiesGeneral

Type of locking (GRP) Door with replaceable hinge Quarter turn locking with two-way key bit

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -55 °C ... 135 °C

MountingAssembly note External fixing clips

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C3 S6 A 382X458X210 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.