

INDUSTRIAL COMPONENT DATA

TC-2KS50-DO32-EX-PR-CS 2905199 PHOENIX CONTACT

Module carrier

Brand: PHOENIX CONTACT | Manufacturer Part Number: TC-2KS50-DO32-EX-PR-CS



Manufacturer	PHOENIX CONTACT
MPN / Reference	TC-2KS50-DO32-EX-PR-CS
Catalog number	2905199
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-97E46160D5
Generated	2026-08-02

Product Overview

Module carrier

Termination Carrier for the redundant connection of 32 MACX Analog Ex-i valve control blocks to digital output cards of the Yokogawa Centum VP control system, via two KS50, 50-pole connectors. Suitable for Yokogawa ADV551 and ADV561 cards.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2905199

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 525 (C-5-2017)

GTIN 4046356950756

Weight per Piece (excluding packing) 333.330 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Nominal voltage UN < 30 V DC (Per signal/channel)

Max. permissible current 1 A (Signal/channel)

Degree of protection IP00

Supply

Designation Power module

Note Supply and error message via 2904673 TC-MACX-MCR-PTB

Input voltage 24 V DC

Input voltage range 19.2 V DC ... 30 V DC

Input current ≤ 2 A

Redundant supply yes, decoupled from diodes

Polarization and surge protection Yes

Output name Switching output

Contact type 1 N/C contact (alarm = open)

Maximum switching voltage 50 V DC (0.3 A)

Fuse 2x 2.5 A on PCB, slow-blow (replaceable)

Status display 1 x red LED (error)

2x green LEDs (PWR1 and PWR2)

Connection 1

Connection name Power supply

Connection method Screw connection

Stripping length 7 mm

Number of connections 1

Number of positions 6

Conductor cross section solid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection 2

Connection name Controller level

Connection method Yokogawa KS-compatible

Number of connections 2

Number of positions 50

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C (Please observe module specifications)

Ambient temperature (storage/transport) -40 °C ... 80 °C

Permissible humidity (operation) 5 % ... 95 % (non-c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TC-2KS50-DO32-EX-PR-CS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.