

INDUSTRIAL COMPONENT DATA

PAI-4-FIX RD 3032732 PHOENIX CONTACT Test adapter

Brand: PHOENIX CONTACT | Manufacturer Part Number: PAI-4-FIX RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	PAI-4-FIX RD
Catalog number	3032732
Category	Test plug for terminal blocks
Minimum order	10 Pcs
Document ID	EO-C2C8C00CA9
Generated	2026-08-02

Product Overview

Test adapter

Test adapter, In plugged in state, safe against finger contact against unintentional direct contact according to DIN EN 50274, for 4 mm test pins and 8.2 mm pitch terminals, number of poles: 1, color: red

Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, number of positions: 1, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesGeneral Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in

General Do not plug in while the power is connected

General Latching testing accessories, therefore only suitable for being plugged in once

Product propertiesProduct type Test socket

Number of positions 1

Data management status

Article revision 08

Electrical propertiesMaximum load current 10 A

Max. voltage 250 V

Connection dataMaximum load current 10 A

Connection method Plug-in connection

DimensionsWidth 5.8 mm

Height 5.8 mm
Depth 51.5 mm
Diameter 5.8 mm
Pin diameter 2.4 mm
Material specifications Color red (RAL 3001)
Material PA
Flammability rating according to UL 94 V0
Insulating material PA
Static insulating material application in cold -60 °C
Relative insulation material temperature index (Elec., UL 746 B) 125 °C
Mechanical properties Mechanical data
Insertion/withdrawal cycles 1
Environmental and real-life conditions Ambient conditions
Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (operation) 20 % ... 90 %
Permissible humidity (storage/transport) 30 % ... 70 %
ETIM for 3032732 Terminal blocks (EC002555)
Feature Name
Feature...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PAI-4-FIX RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.