

INDUSTRIAL COMPONENT DATA

UTRE 6-2/7 3069808 PHOENIX CONTACT Test terminal strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTRE 6-2/7



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTRE 6-2/7
Catalog number	3069808
Category	Test plug for terminal blocks
Minimum order	1 Pcs
Document ID	EO-1F27B11062
Generated	2026-08-03

Product Overview

Test terminal strip

Test pin strip, rated voltage: 400 V, rated current: 24 A, number of connections: 14, number of poles: 7, connection type: Screw connection, 1st floor, Sizing section: 6 mm², cross-section: 0.2 mm² - 10 mm², mounting class: Rail mounting, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 3069808

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 601 (C-1-2017)

GTIN 4055626064949

Weight per Piece (excluding packing) 291.100 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 7

Number of levels 1

Number of connections 14

Potentials 7

Nominal cross section 6 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Test surge voltage 5 kV

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.31 W

Maximum load current 30 A (with 10 mm² conductor cross section)

Current I_{th} 24 A

Nominal voltage UN 400 V AC/DC

Open side panel No

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTRE 6-2/7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.