

INDUSTRIAL COMPONENT DATA

TFKC 2,5/ 2-STF-5,08 AU 1706819 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: TFKC 2,5/ 2-STF-5,08 AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	TFKC 2,5/ 2-STF-5,08 AU
Catalog number	1706819
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-DE0FCFFF74
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Gold, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 4, family of articles: TFKC 2.5/.. -STF, pitch: 5.08 mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Plug component, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 2, pitch: 5.08 mm, connection method: Push-in spring connection, color: green, contact surface: Gold

Your advantages

Gold-plated contacts ensure transfer quality remains stable over the long termTime saving push-in connection, tools not requiredPotentials can be easily looped through - ideal for BUS applicationsIntuitive use through colour coded actuation leverCan be combined with the MSTB 2´,5 rangeScrewable flange for superior mechanical stabilityKey Commercial Data

Orderkey 1706819

Packing unit 1

GTIN 4046356883283

Custom tariff number 85366990

eCI@ss

eCI@ss 4.0 272607xx

eCI@ss 4.1 27260701

eCI@ss 5.0 27260701

eCI@ss 5.1 27260701

eCI@ss 6.0 27260704

eCI@ss 7.0 27440402

eCI@ss 8.0 27440309

eCI@ss 9.0 27440309

ETIM

ETIM 4.0 EC002638

ETIM 5.0 EC002638

ETIM 6.0 EC002638

UNSPSC

UNSPSC 6.01 30211810

UNSPSC 7.0901 39121409

UNSPSC 11 39121409

UNSPSC 12.01 39121409

UNSPSC 13.2 39121409

ETIM for 1706819 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of poles (EF001391)

4

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Angle contact/conductor connection (EF007546)

Other

Rated current I_n (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TFKC 2,5/ 2-STF-5,08 AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.