

INDUSTRIAL COMPONENT DATA

MINI MCR-SL-PTB-FM 2902958 PHOENIX CONTACT Power terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI MCR-SL-PTB-FM



Manufacturer	PHOENIX CONTACT
MPN / Reference	MINI MCR-SL-PTB-FM
Catalog number	2902958
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-B82FCC7A28
Generated	2026-08-06

Product Overview

Power terminal block

The MINI MCR-SL-PTB-FM(-SP) power terminal block is inserted into the rail connector to supply the supply voltage. The FM power terminal offers the additional monitoring function together with the fault monitoring module. Screw connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2902958

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 524 (C-5-2017)

GTIN 4046356702713

Weight per Piece (excluding packing) 82.100 g

Custom tariff number 85369010

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 93.1 mm

Depth 102.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 65 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Output data

Output voltage range Input voltage - 0.8 V

General

Mounting position any

Assembly instructions The T connector can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail according to EN 60715.

Connection data, input

Connection method Screw connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 12

Stripping length 12 mm

Screw thread M3

Standards and Regulations

Electromagnetic compatibility Conformance with EMC directive

Noise emission EN 61000-6-4

Standards/regulations EN 61000-4-2

Designation Electromagnetic RF field

Standards/regulations EN 61000-4-3

Evaluation criterion A

Standards/regulations EN 61000-4-4

EN 61000-4-5

Designation Conducted interferences

Standards/regulations EN 61000-4-6

Evaluation criterion A

Confo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI MCR-SL-PTB-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.